

FEATURES

- Fully automatic (one button) or manual casting cycle
- Built-in vacuum pump and inert gas (argon or nitrogen) circuit
- Coil rotation with arm and flask metal is continuously heated and injected while the coil rotates
- Accurate temperature reader with advanced temperature controller and metal emissivity regulation
- Allows casting with precious stones in place
- Advanced, highly efficient induction heating technology
- Modern 5" full color LCD touch control panel
- Multiple user programs with many pre-programmed settings
- Special programs for titanium casting (Supercast J5 models)
- Easy to install and very simple and safe to operate

SuperCast J is an advanced universal casting machine which utilizes the patented Rotating Coil System (RCS). The RCS continues to melt the metal while spinning and injecting. This way, the system maintains the molten metal's viscosity during casting and prevents premature solidification due to coil lifting and injection delays. The unique feature guarantees perfect casting results with high-temperature, fast solidifying metals such as Platinum. Palladium and Titanium.

Our popular high-end Supercast J models are fully automatic and can cast with excellent quality and repeatability all precious and non-precious metals and alloys. The powerful motor with high acceleration and speed guarantees very low porosity and high compacting of the metal. Advanced high-frequency induction heating generator provides fast and efficient melting and mixing of all metals in grains, ingots, scrap or powder form.

The modern LCD Touch control panel features an easy to use interface and provides intuitive and informative visual feedback. It displays the measured process parameters, receives user input, sets various parameters and saves multiple programs. It also displays diagnostic and warning messages.

APPLICATIONS

Casting-centrigugal

HEADQUARTERS

10 Colt Court Ronkonkoma, New York 11779 Tel: 631.467.6814 sales@ultraflexpower.com













BENEFITS

- Improved energy efficiency
- Higher degree of controllability
- Increased repeatability

- Low maintenance requirements
- Increased productivity

SPECIFICATION

	Supercast Lite J4 0UPT-017-350	Supercast Plus J5-T 0UPT-017-450
Absorbed Power kW (max)	4.0 kW	5.0 kW
AC Line Volts (50/60Hz)), 1 Phase	230±10%	230±10%
Max Melting T°	2000 C°	2000 C°
Crucible Capacity	200g Pt (50g Pt min), 170g Au, 80g Ag	200g Pt (50g Pt min), 170g Au 80g Ti (min 10g Ti – ingot), 80g Ag
Crucible Volume	Graphite insert 10 cm3 Ceramic 30 cm3	Graphite insert 10 cm3 Ceramic 30 cm3
Flask Size (max), DxH	80 mm x 75 mm	90 mm x 90 mm
Water Cooling System	included	included
Vacuum Pump	included	included
Auto-Cast Programs	No	included
Titanium casting program	No	Yes
LCD touch control panel	No	Yes
Weight Lb (kg)	155 kg (342 Lb)	175 kg (385.8 Lb)
Dimensions Inch (cm) WxDxH	25.2" x 26.4" x 41.3" (64 x 67 x 105)	25.2" x 26.4" x 41.3" (64 x 67 x 105)

HEADQUARTERS

10 Colt Court Ronkonkoma, New York 11779 Tel: 631.467.6814 sales@ultraflexpower.com











